



## Marathon Petroleum Company LP

539 South Main Street  
Findlay, OH 45840  
Telephone 419-421-3070



**RESPONSIBLE CARE®**  
OUR COMMITMENT TO SUSTAINABILITY

Customer ID: 0000303772

1/16/2018

HEATH OIL INC  
P O BOX 1128  
OIL CITY, PA 163010000

MSDS Enclosed For

Product Id	Product Name
0121MAR019	Marathon Petroleum K-1 Kerosene

Dear Customer or Product User,

Marathon Petroleum Company LP (Marathon), a Responsible Care® company, is committed to supplying *quality products and safe handling and use information*. Thank you for allowing us to be your chosen supplier! This mailing is intended to ensure that your organization has the most current Safety Data Sheets (SDS) for Marathon products.

We firmly believe that being a proper steward of our products is of utmost importance, and *therefore want to help you to understand how to specifically manage our products as to their potential health, safety and environmental impacts*. Toward that end, Marathon distributes and makes available SDSs on our website ([www.marathonpetroleum.com/brand/Products/SDS/](http://www.marathonpetroleum.com/brand/Products/SDS/)) that provide safety, health, and environmental information. An "Explanation of Terms" sheet is also included to aid your understanding of the terms and abbreviations used in each SDS.

Marathon's SDSs satisfy the requirements of OSHA's Hazard Communication Standard (29 CFR 1910.1200) and state and federal worker "Right-to-Know" regulations. OSHA requires employers to make SDSs available to their employees and customers. In addition, SDSs contain information that is necessary to comply with various provisions of the EPA's Emergency Planning and Community Right-to-Know Act, 40 CFR 370 (SARA Title III).

If you have any questions or comments on our intended product applications, exposure potential and/or hazards or safe handling information, please contact us at the number or e-mail address listed below. If you are not directly involved with the retention of SDSs, please forward the enclosed SDS to the appropriate person in your organization. Also, in the future if you prefer to have SDSs sent via e-mail, if you need to change your address, or to update your organization's contact person for SDSs, please let us know.

Thank you for your continued business!

**SDS Inquiries**

Hazard Communication Coordinator: (419) 421-3070

[sdsinfo@marathonpetroleum.com](mailto:sdsinfo@marathonpetroleum.com)



# MARATHON PETROLEUM COMPANY LP

## SAFETY DATA SHEET(SDS) TERMS & MEANINGS

### SECTION 1 IDENTIFICATION

**SDS ID NO.:** Number assigned in the WerCS Studio® database for each product.

**SDS Revision Date:** Date that an SDS was significantly updated or changed and a revision was issued.

**Name:** Most common name or name under which a product is marketed.

**Synonyms:** Other common chemical or commercial names (aliases) used to identify a product.

**Chemical Family:** Generic chemical classification or family for a product.

**Emergency Phone Numbers:** 24 hour / 7 Day emergency assistance number, e.g. accident or spill support.

### SECTION 2 HAZARD IDENTIFICATION

OSHA (Occupational Safety & Health Administration) hazard status with physical and chemical hazard classifications according to 2012 Hazard Communication Standard (29CFR1910.1200) criteria.

**Emergency Overview:** Indicates a product's characteristics, appearance, most significant hazards, pictograms and precautionary statements.

### SECTION 3 COMPOSITION

Composition with assigned Chemical Abstracts Service (CAS) Registry numbers and component concentrations. CAS numbers provide a unique, unmistakable identifier for chemical substances

### SECTION 4 FIRST AID MEASURES

Recommended immediate care based on the route of exposure and includes the most prominent adverse effects for an overexposed, ill or injured person. Treatment is usually at the scene of the incident, possibly by non-medically trained personnel in an attempt to save lives or to prevent and/or retard further illness or injury. Advice on special treatment and cautions are also provided for physicians.

### SECTION 5 FIRE FIGHTING MEASURES

National Fire Protection Association (NFPA) ratings are listed for Health, Flammability and Instability according to NFPA publication #704. Flammability Ratings are as follows: Highly Flammable = 4, Flammable = 3, Combustible = 2, Not Combustible = 1.

### SECTION 7 HANDLING AND STORAGE

**Static Accumulator:** A low conductivity liquid, typically with a conductivity less than 50 pS/m (picoSiemens per meter), capable of accumulating a static charge during transfer or storage. Refer to API Recommended Practice (RP) 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents.

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits are listed for concentrations of the product or components in parts of material per million parts of air (ppm) or milligrams of material per cubic meter of air (mg/M<sup>3</sup>). **PELs** (Permissible Exposure Limits) are OSHA regulatory limits on exposure to concentrations of substances in the air and are based on an 8-hour time weighted average (TWA) exposures. A "skin" designation refers to the potential contribution to the overall exposure by the dermal route and serves as a warning that skin absorption should be prevented in order to avoid exceeding the absorbed dose received by inhalation at the PEL. **TLVs** (Threshold Limit Values) are consensus occupational exposure limits on exposure to concentrations of substances in the air from the American Conference of Governmental Industrial Hygienists (ACGIH) of which three categories exist: **TWA** is the time-weighted average air concentration for a normal 8 hour workday and a 40 hour work week to which nearly all workers may be repeatedly exposed without adverse effect; **STEL** or short term exposure limit is a 15 minute time-weighted average of air concentration which should not be exceeded at any time during a workday and not repeated more than four times a day and; **C** (Ceiling limit) is a concentration in air that should not be exceeded at any time during the work period. **IDLH** (Immediately Dangerous to Life or Health) from the US National Institute for Occupational Safety and Health (NIOSH) is an airborne exposure concentration that is "likely to cause death or immediate or delayed permanent adverse health effects or prevent escape from such an environment."



## **SECTION 9 PHYSICAL & CHEMICAL PROPERTIES**

**Flash Point:** Minimum temperature at which a liquid will give off enough flammable vapor to form an ignitable mixture with air.

**Boiling Point:** Temperature (or range) at a pressure of 760 mm Hg, where a liquid changes to a vapor.

**Explosive Limits:** Lower and upper range of a gas or vapor concentration which will burn or explode if an ignition source is present.

**Auto-ignition Temperature:** Lowest temperature at which the product will initiate self-sustained combustion in the absence of a spark or flame.

**Specific Gravity:** Ratio of the weight of a volume of product to the weight of an equal volume of water at 39.2°F (4°C).

**Vapor Density:** Relative density or weight of a vapor or gas compared with an equal volume of air at ambient temperatures.

**Vapor Pressure:** Pressure of saturated vapor above a liquid product in mm Hg at a specific temperature.

**Water Solubility:** According to %weight/volume at a specified temperature. Classes include: Negligible = <0.1%, Slight = 0.1-1.0%, Moderate = 1-10%, Appreciable = >10%, Complete.

**Melting Point:** Temperature (or range) at a pressure of 760 mm Hg, where a solid changes to a liquid.

**Partition Coefficient (K<sub>ow</sub>):** At a specified temperature, the ratio of the concentration of a chemical in n-octanol and water at equilibrium

**pH:** a logarithmic measure of hydrogen ion concentration (0-14) of a substance in aqueous solution and an indication of its acidity (<7) or alkalinity (>7). Pure water has a pH very close to 7.

**VOC Content (%):** Generally, the percent concentration of the sum of Volatile Organic (Carbon) Compounds in a material excluding carbon monoxide and carbon dioxide. Petroleum hydrocarbons that have carbon chain lengths >12 have very low VOC concentrations, e.g. <1%.

## **SECTION 10 STABILITY & REACTIVITY**

**Incompatible Materials:** Those materials or conditions that may cause the product to react violently, releasing large amounts of energy or toxic vapors.

**Hazardous Polymerization:** Indication that the product has the potential to have a reaction at a rate that releases large amounts of energy. Conditions that could promote polymerization are listed.

## **SECTION 11 TOXICOLOGICAL INFORMATION**

Potential acute/short/immediate, delayed or long-term (chronic) adverse health effects by different routes of exposure are described that are either confirmed or suspected, based on observations in humans, animal studies or by deduction from the effects that occur from overexposure to a similar substance.

**Acute:** Abrupt, rapidly evident health effects due to single or short-term exposures that are usually observed at high levels or concentrations.

**LD<sub>50</sub> (Lethal Dose 50%):** Single acute dose or range of a material that produces death in 50% of the test animals by the oral or dermal routes of exposure.

**LC<sub>50</sub> (Lethal Concentration 50%):** Single acute inhalation exposure concentration or range of a material in the air over a specified time period that produces death in 50% of the test animals.

**Delayed:** Health effects that are manifested after some period of time has passed following the exposure

**Chronic:** Insidious, slowly evident health effects due to repeated or long-term exposures usually to lower levels or concentrations than those producing acute effects.

**Carcinogenicity:** Listed classifications for cancer potential:

**ACGIH** (American Conference of Governmental Industrial Hygienists): A1 = Known Human Carcinogen; A2 = Suspected Human Carcinogen; A3 = Animal Carcinogen; A4 = Not Classifiable

**IARC** (International Agency for Research on Cancer): Group #1 = Carcinogenic to Humans; 2A = Probably Carcinogenic to Humans; 2B = Probably Carcinogenic to Humans; 3 = Not Classifiable for Carcinogenicity

**NTP** (National Toxicology Program): Known Carcinogen; Reasonably Anticipated to be a Human Carcinogen

**OSHA** (Occupational Safety & Health Administration): Classified as a carcinogen (29CFR1910.1200 App. F)

**Mutagenic effects:** Heritable genetic changes that may increase the frequency of mutations.

**Sensitization:** Bodily process where, after an initial exposure to a sensitizing chemical, the immune system is provoked to produce allergic responses to even small amounts of that chemical with subsequent exposures.

## **SECTION 12 ECOLOGICAL INFORMATION**

Ecotoxicity refers to the property of chemicals to adversely affect the environment and the plants and animals living in it.

**LC<sub>50</sub> (Lethal Concentration):** Single acute exposure to an aqueous concentration or range of a material over a specified time period that produces death in 50% of the test population.

**EC<sub>50</sub> (Effective Concentration):** Single acute exposure to an aqueous concentration or range of a material over a specified period of time that effects at least 50% of the test population.

**WAF (Water Accommodated Fraction):** An aqueous fraction containing the dissolved, suspended and/or emulsified fraction of a multi-component/complex substances or a mixture. WAFs maximize the aqueous solubility of test materials.

**Readily Biodegradable:** Applies to materials having a 60 percent or greater degradation in 28 days

**Inherently Biodegradable:** Applies to materials having a maximum half-life of 60 days or less.

5/15/2015





# SAFETY DATA SHEET

SDS ID NO.: 0121MAR019  
Revision Date 05/26/2016

## 1. IDENTIFICATION

**Product Name:** Marathon Petroleum K-1 Kerosene

**Synonym:** Kerosene; K-1 Kerosene 400 ppm Sulfur Max; K-1 Kerosene 500 ppm Sulfur Max; Kerosene K-1; K-1 Kerosene, Non-Road Use, Undyed; Kerosine

**Product Code:** 0121MAR019

**Chemical Family:** Complex Hydrocarbon Substance

**Recommended Use:** Fuels.

**Restrictions on Use:** All others.

**Manufacturer, Importer, or Responsible Party Name and Address:**  
**MARATHON PETROLEUM COMPANY LP**  
**539 South Main Street**  
**Findlay, OH 45840**

**SDS information:** 1-419-421-3070

**Emergency Telephone:** 1-877-627-5463

## 2. HAZARD IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Acute aquatic toxicity	Category 2
Chronic aquatic toxicity	Category 2

#### Hazards Not Otherwise Classified (HNOC)

Static accumulating flammable liquid

### Label elements

#### EMERGENCY OVERVIEW

#### Danger

#### FLAMMABLE LIQUID AND VAPOR

May accumulate electrostatic charge and ignite or explode  
May be fatal if swallowed and enters airways  
Causes skin irritation

May cause respiratory irritation  
 May cause drowsiness or dizziness  
 Suspected of causing cancer  
 Toxic to aquatic life with long lasting effects



**Appearance** Clear or Amber Liquid

**Physical State** Liquid

**Odor** Slight Hydrocarbon

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Wash hands and any possibly exposed skin thoroughly after handling  
 Avoid release to the environment

#### Precautionary Statements - Response

IF exposed or concerned: Get medical attention  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 If skin irritation occurs: Get medical attention  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor if you feel unwell  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor  
 Do NOT induce vomiting  
 In case of fire: Use water spray, fog or regular foam for extinction  
 Collect spillage

#### Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed  
 Keep cool  
 Store locked up

#### Precautionary Statements - Disposal

Dispose of contents/container at an approved waste disposal plant

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

1-K Kerosine is a complex mixture of paraffins, cycloparaffins, olefins and aromatic hydrocarbons having hydrocarbon chain lengths predominantly in the range of nine to sixteen carbons. May contain a trace amount of benzene (<0.01%). Contains a trace amount of sulfur (15-400 ppm).

#### Composition Information:

Name	CAS Number	% Concentration
Kerosine (petroleum)	8008-20-6	100



Naphthalene	91-20-3	0.3-2.6
-------------	---------	---------

All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

## 4. FIRST AID MEASURES

### First Aid Measures

- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show directions for use or safety data sheet if possible).
- Inhalation:** Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, ensure airway is clear, give oxygen and continue to monitor. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). Keep affected person warm and at rest. If symptoms occur get medical attention.
- Skin Contact:** Immediately wash exposed skin with plenty of soap and water while removing contaminated clothing and shoes. May be absorbed through the skin in harmful amounts. Get medical attention if irritation persists. Any injection injury from high pressure equipment should be evaluated immediately by a physician as potentially serious (See NOTES TO PHYSICIAN).
- Place contaminated clothing in closed container until cleaned or discarded. If clothing is to be laundered, inform the person performing the operation of contaminant's hazardous properties. Destroy contaminated, non-chemical resistant footwear.
- Eye Contact:** Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Gently remove contacts while flushing. Get medical attention if irritation persists.
- Ingestion:** Do not induce vomiting because of danger of aspirating liquid into lungs, causing serious damage and chemical pneumonitis. If spontaneous vomiting occurs, keep head below hips, or if patient is lying down, turn body and head to side to prevent aspiration and monitor for breathing difficulty. Never give anything by mouth to an unconscious person. Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.

### Most important signs and symptoms, both short-term and delayed with overexposure

- Adverse Effects:** Irritating to the skin and mucous membranes. Symptoms may include redness, itching, and inflammation. May cause nausea, vomiting, diarrhea, and signs of nervous system depression: headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Aspiration hazard. May cause coughing, chest pains, shortness of breath, pulmonary edema and/or chemical pneumonitis. Repeated or prolonged skin contact may cause drying, reddening, itching and cracking.

### Indication of any immediate medical attention and special treatment needed

- Notes To Physician:**
- INHALATION:** This material (or a component) sensitizes the myocardium to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.
- SKIN:** Leaks or accidents involving high-pressure equipment may inject a stream of material through the skin and initially produce an injury that may not appear serious. Only a small puncture wound may appear on the skin surface but, without proper treatment and depending on the nature, original pressure, volume, and location of the injected material, can compromise blood supply to an affected body part. Prompt surgical debridement of the wound may be necessary to prevent irreversible loss of function and/or the affected body part. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES.
- INGESTION:** This material represents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended.

## 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

For small fires, Class B fire extinguishing media such as CO<sub>2</sub>, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Firefighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

### Unsuitable extinguishing media

Do not use straight water streams to avoid spreading fire.

### Specific hazards arising from the chemical

This product has been determined to be a flammable liquid per the OSHA Hazard Communication Standard and should be handled accordingly. May accumulate electrostatic charge and ignite or explode. Vapors may travel along the ground or be moved by ventilation and ignited by many sources such as pilot lights, sparks, electric motors, static discharge, or other ignition sources at locations distant from material handling. Flashback can occur along vapor trail. For additional fire related information, see NFPA 30 or the Emergency Response Guidebook 128.

### Hazardous combustion products

Smoke, carbon monoxide, and other products of incomplete combustion.

### Explosion data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

### Special protective equipment and precautions for firefighters

Firefighters should wear full protective clothing and positive-pressure self-contained breathing apparatus (SCBA) with a full face-piece, as appropriate. Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Keep run-off water out of sewers and water sources.

### Additional firefighting tactics

**FIRES INVOLVING TANKS OR CAR/TRAILER LOADS:** Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after the fire is out. Do not direct water at source of leak or safety devices; icing may occur. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**EVACUATION:** Consider initial downwind evacuation for at least 1000 feet. If tank, rail car or tank truck is involved in a fire, ISOLATE for 5280 feet (1 mile) in all directions; also, consider initial evacuation of 5280 feet (1 mile) in all directions.

### NFPA

Health 1

Flammability 2

Instability 0

Special Hazard -

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions:

Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Eliminate all ignition sources. All contaminated surfaces will be slippery.

### Protective equipment:

Use personal protection measures as recommended in Section 8.

### Emergency procedures:

Advise authorities and National Response Center (800-424-8802) if the product has entered a water course or sewer. Notify local health and pollution control agencies, if appropriate.

### Environmental precautions:

Avoid release to the environment. Avoid subsoil penetration.

### Methods and materials for containment:

Contain liquid with sand or soil. Prevent spilled material from entering storm drains, sewers, and open waterways.

### Methods and materials for cleaning

Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual



up: liquids. Recover and return free product to proper containers. When recovering free liquids ensure all equipment is grounded and bonded. Use only non-sparking tools.

## 7. HANDLING AND STORAGE

### Safe Handling Precautions:

NEVER SIPHON THIS PRODUCT BY MOUTH. Use appropriate grounding and bonding practices. Static accumulating flammable liquid. Bonding and grounding may be insufficient to eliminate the hazard from static electricity. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Vapors may travel along the ground or be moved by ventilation. Flashback may occur along vapor trails. No smoking. Use only non-sparking tools. Avoid repeated and prolonged skin contact. Avoid breathing vapors or mists. Use only with adequate ventilation. Use personal protection measures as recommended in Section 8. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water. Do not cut, drill, grind or weld on empty containers since explosive residues may remain. Refer to applicable EPA, OSHA, NFPA and consistent state and local requirements.

Hydrocarbons are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering, pumping at high flow rates or loading and transfer operations. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Sudden release of hot organic chemical vapors or mists from process equipment operating under elevated temperature and pressure, or sudden ingress of air into vacuum equipment may result in ignition of vapors or mists without the presence of obvious ignition sources. Nozzle spouts must be kept in contact with the containers or tank during the entire filling operation.

Portable containers should never be filled while in or on a motor vehicle or marine craft. Containers should be placed on the ground. Static electric discharge can ignite fuel vapors when filling non-grounded containers or vehicles on trailers. The nozzle spout must be kept in contact with the container before and during the entire filling operation. Use only approved containers.

A buildup of static electricity can occur upon re-entry into a vehicle during fueling especially in cold or dry climate conditions. The charge is generated by the action of dissimilar fabrics (i.e., clothing and upholstery) rubbing across each other as a person enters/exits the vehicle. A flash fire can result from this discharge if sufficient flammable vapors are present. Therefore, do not get back in your vehicle while refueling.

Cellular phones and other electronic devices may have the potential to emit electrical charges (sparks). Sparks in potentially explosive atmospheres (including fueling areas such as gas stations) could cause an explosion if sufficient flammable vapors are present. Therefore, turn off cellular phones and other electronic devices when working in potentially explosive atmospheres or keep devices inside your vehicle during refueling.

High-pressure injection of any material through the skin is a serious medical emergency even though the small entrance wound at the injection site may not initially appear serious. These injection injuries can occur from high-pressure equipment such as paint spray or grease or guns, fuel injectors, or pinhole leaks in hoses or hydraulic lines and should all be considered serious. High pressure injection injuries may be SERIOUS SURGICAL EMERGENCIES (See First Aid Section 4).

### Storage Conditions:

Store in properly closed containers that are appropriately labeled and in a cool, well-ventilated area. Do not store near an open flame, heat or other sources of ignition.

### Incompatible Materials

Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	ACGIH TLV	OSHA PELs:	OSHA - Vacated PELs	NIOSH IDLH
Kerosine (petroleum) 8008-20-6	200 mg/m <sup>3</sup> TWA Skin - potential significant	-	-	-



	contribution to overall exposure by the cutaneous route			
Naphthalene 91-20-3	10 ppm TWA Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup>	10 ppm TWA 50 mg/m <sup>3</sup> TWA 15 ppm STEL 75 mg/m <sup>3</sup> STEL	250 ppm

**Notes:** The manufacturer has voluntarily elected to provide exposure limits contained in OSHA's 1989 air contaminants standard in its SDSs, even though certain of those exposure limits were vacated in 1992.

**Engineering measures:** Local or general exhaust required in an enclosed area or with inadequate ventilation. Use mechanical ventilation equipment that is explosion-proof.

#### Personal protective equipment

**Eye protection:** Use goggles or face-shield if the potential for splashing exists.

**Skin and body protection:** Wear neoprene, nitrile or PVA gloves to prevent skin contact. Glove suitability is based on workplace conditions and usage. Contact the glove manufacturer for specific advice on glove selection and breakthrough times.

**Respiratory protection:** Use a NIOSH approved organic vapor chemical cartridge or supplied air respirators when there is the potential for airborne exposures to exceed permissible exposure limits or if excessive vapors are generated. Observe respirator assigned protection factors (APFs) criteria cited in federal OSHA 29 CFR 1910.134. Self-contained breathing apparatus should be used for fire fighting.

**Hygiene measures:** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical State	Liquid
Appearance	Clear or Amber Liquid
Color	Clear or Amber
Odor	Slight Hydrocarbon
Odor Threshold	No data available.

<u>Property</u>	<u>Values (Method)</u>
Melting Point / Freezing Point	-56 to -39 °C / -68 to -39 °F (ASTM D5949)
Initial Boiling Point / Boiling Range	134-294 °C / 274-562 °F (ASTM D86)
Flash Point	46-71 °C / 116-159 °F (ASTM D93)
Evaporation Rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammability Limit in Air (%):	
Upper Flammability Limit:	5.0
Lower Flammability Limit:	0.4
Explosion limits:	No data available.
Vapor Pressure	No data available.
Vapor Density	No data available.
Specific Gravity / Relative Density	0.70-0.82
Water Solubility	No data available.
Solubility in other solvents	No data available.
Partition Coefficient	No data available.
Decomposition temperature	No data available.
pH:	Not applicable
Autoignition Temperature	210 °C / 410 °F
Kinematic Viscosity	1.37-1.72 cSt @ 40°C (ASTM D445)
Dynamic Viscosity	No data available.



Explosive Properties	No data available.
VOC Content (%)	No data available.
Density	No data available.
Bulk Density	Not applicable.

## 10. STABILITY AND REACTIVITY

<u>Reactivity</u>	The product is non-reactive under normal conditions.
<u>Chemical stability</u>	The material is stable at 70°F (21°C), 760 mmHg pressure.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Hazardous polymerization</u>	Will not occur.
<u>Conditions to avoid</u>	Excessive heat, sources of ignition, open flame.
<u>Incompatible Materials</u>	Strong oxidizing agents.
<u>Hazardous decomposition products</u>	None known under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Potential short-term adverse effects from overexposures

<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness or dizziness. <i>Breathing high concentrations of this material, for example, in a confined space or by intentional abuse, can cause irregular heartbeats which can cause death.</i>
<b>Eye contact</b>	Exposure to vapor or contact with liquid may cause mild eye irritation, including tearing, stinging, and redness.
<b>Skin contact</b>	Causes skin irritation. Effects may become more serious with repeated or prolonged contact. May be absorbed through the skin in harmful amounts.
<b>Ingestion</b>	May be fatal if swallowed or vomited and enters airways. May cause irritation of the mouth, throat and gastrointestinal tract.

### Acute toxicological data

Name	Oral LD50	Dermal LD50	Inhalation LC50
Kerosine (petroleum) 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Naphthalene 91-20-3	490 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 340 mg/m <sup>3</sup> (Rat) 1 h

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

MIDDLE DISTILLATES, PETROLEUM: Long-term repeated (lifetime) skin exposure to similar materials has been reported to result in an increase in skin tumors in laboratory rodents. The relevance of these findings to humans is not clear at this time. Altered mental state, drowsiness, peripheral motor neuropathy, irreversible brain damage (so-called Petrol Sniffer's Encephalopathy), delirium, seizures, and sudden death have been reported from repeated overexposure to some hydrocarbon solvents, naphthas, and gasoline.

ISOPARAFFINS: Studies in laboratory animals have shown that long-term exposure to similar materials (isoparaaffins) can cause kidney damage and kidney cancer in male laboratory rats. However, in-depth research indicates that these findings are unique to the male rat, and that these effects are not relevant to humans.

NAPHTHALENE: Severe jaundice, neurotoxicity (kernicterus) and fatalities have been



reported in young children and infants as a result of hemolytic anemia from overexposure to naphthalene. Persons with glucose 6-phosphate dehydrogenase (G6PD) deficiency are more prone to the hemolytic effects of naphthalene. Adverse effects on the kidney have been reported in persons overexposed to naphthalene but these effects are believed to be a consequence of hemolytic anemia, and not a direct effect. Hemolytic anemia has been observed in laboratory animals exposed to naphthalene. Laboratory rodents exposed to naphthalene vapor for 2 years (lifetime studies) developed non-neoplastic and neoplastic tumors and inflammatory lesions of the nasal and respiratory tract. Cataracts and other adverse effects on the eye have been observed in laboratory animals exposed to high levels of naphthalene. Findings from a large number of bacterial and mammalian cell mutation assays have been negative. A few studies have shown chromosomal effects (elevated levels of Sister Chromatid Exchange or chromosomal aberrations) in vitro. Naphthalene has been classified as Possibly Carcinogenic to Humans (2B) by IARC, based on findings from studies in laboratory animals.

**DIESEL EXHAUST:** The combustion of diesel fuels produces gases including carbon monoxide, carbon dioxide, oxides of nitrogen and/or sulfur, and hydrocarbons that can be irritating and hazardous with overexposure. Long-term occupational overexposure to diesel exhaust and diesel exhaust particulate matter has been associated with an increased risk of respiratory disease, including lung cancer, and is characterized as a "known human carcinogen" by the International Agency for Research on Cancer (IARC), as "a reasonably anticipated human carcinogen" by the National Toxicology Program, and as "likely to be carcinogenic to humans" by the EPA, based upon animal and occupational exposure studies. However, uncertainty exists with these classifications because of deficiencies in the supporting occupational exposure/epidemiology studies, including reliable exposure estimates. Lifetime animal inhalation studies with pulmonary overloading exposure concentrations of diesel exhaust emissions have produced tumors and other adverse health effects. However, in more recent long-term animal inhalation studies of diesel exhaust emissions, no increase in tumor incidence and in fact a substantial reduction in adverse health effects along with significant reductions in the levels of hazardous material emissions were observed and are associated with fuel composition alterations coupled with new technology diesel engines.

#### Adverse effects related to the physical, chemical and toxicological characteristics

##### Signs and Symptoms

Irritating to the skin and mucous membranes. Symptoms may include redness, itching, and inflammation. May cause nausea, vomiting, diarrhea, and signs of nervous system depression: headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Aspiration hazard. May cause coughing, chest pains, shortness of breath, pulmonary edema and/or chemical pneumonitis. Repeated or prolonged skin contact may cause drying, reddening, itching and cracking.

##### Sensitization

Not expected to be a skin or respiratory sensitizer.

##### Mutagenic effects

None known.

##### Carcinogenicity

Cancer designations are listed in the table below

Name	ACGIH (Class)	IARC (Class)	NTP	OSHA
Kerosine (petroleum) 8008-20-6	Confirmed animal carcinogen (A3)	Not Classifiable (3)	Not Listed	Not Listed
Naphthalene 91-20-3	Confirmed animal carcinogen (A3)	Possible human carcinogen (2B)	Reasonably anticipated to be a human carcinogen	Not Listed

##### Reproductive toxicity

None known.

##### Specific Target Organ Toxicity (STOT) - single exposure

Respiratory system. Central nervous system.

##### Specific Target Organ Toxicity (STOT) - repeated exposure

Not classified.

##### Aspiration hazard

May be fatal if swallowed or vomited and enters airways.



## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

This product should be considered toxic to aquatic organisms, with the potential to cause long lasting adverse effects in the aquatic environment.

Name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Kerosine (petroleum) 8008-20-6	72-hr EL50 = 5.0-11 mg/l Algae	96-hr LL50 = 18-25 mg/l Fish	-	48-hr EL50 = 1.4-21 mg/l Invertebrates
Naphthalene 91-20-3	-	96-hr LC50 = 0.91-2.82 mg/l Rainbow trout (static) 96-hr LC50 = 1.99 mg/l Fathead minnow (static)	-	48-hr LC50 = 1.6 mg/l Daphnia magna

### Persistence and degradability

Expected to be inherently biodegradable.

### Bioaccumulation

Has the potential to bioaccumulate.

### Mobility in soil

May partition into air, soil and water.

### Other adverse effects

No information available.

## 13. DISPOSAL CONSIDERATIONS

### Description of Waste Residues

This material may be a flammable liquid waste.

### Safe Handling of Wastes

Handle in accordance with applicable local, state, and federal regulations. Use personal protection measures as required. Use appropriate grounding and bonding practices. Use only non-sparking tools. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. No smoking.

### Disposal of Wastes / Methods of Disposal

The user is responsible for determining if any discarded material is a hazardous waste (40 CFR 262.11). Dispose of in accordance with federal, state and local regulations.

### Methods of Contaminated Packaging Disposal

Empty containers should be completely drained and then discarded or recycled, if possible. Do not cut, drill, grind or weld on empty containers since explosive residues may be present. Dispose of in accordance with federal, state and local regulations.

## 14. TRANSPORT INFORMATION

### DOT (49 CFR 172.101):

UN Proper Shipping Name:	Kerosene
UN/Identification No:	UN 1223
Class:	3
Packing Group:	III

### TDG (Canada):

UN Proper Shipping Name:	Kerosene
UN/Identification No:	UN 1223
Transport Hazard Class(es):	3
Packing Group:	III

## 15. REGULATORY INFORMATION

### US Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b):

This product and/or its components are listed on the TSCA

## Chemical Inventory.

## EPA Superfund Amendment &amp; Reauthorization Act (SARA):

**SARA Section 302:** This product does not contain any component(s) included on EPA's Extremely Hazardous Substance (EHS) List.

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Kerosine (petroleum)	NA
Naphthalene	NA

**SARA Section 304:** This product may contain component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	Hazardous Substances RQs
Kerosine (petroleum)	NA
Naphthalene	100 lb final RQ 45.4 kg final RQ

**SARA Section 311/312:** The following EPA hazard categories apply to this product:

Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

**SARA Section 313:** This product may contain component(s), which if in exceedance of the de minimus threshold, may be subject to the reporting requirements of SARA Title III Section 313 Toxic Release Reporting (Form R).

Name	CERCLA/SARA 313 Emission reporting:
Kerosine (petroleum)	None
Naphthalene	0.1 % de minimis concentration

## State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

## Kerosine (petroleum)

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	SN 1091
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To-Know:	Present
Florida Substance List:	Not Listed
Rhode Island Right-To-Know:	Not Listed
Michigan Critical Materials Register List:	Not Listed
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	SN 1091 TPQ: 10000 lb (Under N.J.A.C. 7:1G, environmental hazardous substances in mixtures such as gasoline or new and used petroleum oil may be reported under these categories)
Illinois - Toxic Air Contaminants:	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

## Naphthalene

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Carcinogen, initial date 4/19/02
New Jersey Right-To-Know:	SN 1322 SN 3758
Pennsylvania Right-To-Know:	Environmental hazard Present (particulate)
Massachusetts Right-To-Know:	Present



Florida Substance List:	Not Listed
Rhode Island Right-To-Know:	Toxic; Flammable
Michigan Critical Materials Register List:	Not Listed
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Carcinogen
New Jersey - Environmental Hazardous Substances List:	SN 1322 TPQ: 500 lb (Reportable at the de minimis quantity of >0.1%)
Illinois - Toxic Air Contaminants:	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	100 lb RQ (air); 1 lb RQ (land/water)

**Canada DSL/NDL Inventory:** This product and/or its components are listed either on the Domestic Substances List (DSL) or are exempt.

**Canadian Regulatory Information:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Kerosine (petroleum)	B3,D2B	1%
Naphthalene	B4,D2A	0.1%



**Note:** Not applicable.

## 16. OTHER INFORMATION

**Prepared By** Toxicology and Product Safety

### Revision Notes

**Revision Date** 05/26/2016

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is intended as guidance for safe handling, use, processing, storage, transportation, accidental release, clean-up and disposal and is not considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.